







1180 - 1265

630 665 D

SH 430 - 515 SW 485

460 SD

AW 460

BW 660



U10M-NH1-M21B116-73A-R2 MANAGERIAL MID BACK SYNCHRON CHAIR

630

D SH 430 - 515 SW 485

SD 460 BW 660 AW 460



U10M-NB5-M21B116-42A-R2 MANAGERIAL MID BACK SYNCHRON CHAIR

1005 - 1105 645

SH 440 - 540 SW 485

D

SD 460 BW 675 AW 460

*All Dimension in mm

SD : Seat Depth W : Overall Width SH : Seat Height D : Overall Depth H : Overall Height BW : Base Width SW: Seat Width AW : Armrest Inner Width

VISITOR MID BACK CHAIR

610 590 D SH 480

U10V-CE42-B117-42A

460 BW 485 AW 460

Our products are manufactured under stringent quality controls and is recipient of ISO 9001:2008 quality assurance With the constant upgrading of products,

PERFECT U reserves the right to make appropriate changes of specification without any





Features & Benefits

1 Seat Height Adjustment

- lift right-hand lever up to adjust the seat height without sitting on the chair.
- To lower seat height, lift right-hand lever up while seated. - For optimal posture, thighs should be
- comfort.
- Push in the right-hand lever to lock the seat position. - Pull outwards the lever to unlock.
- The mechanism provides dynamic seating which maintains support as you move and recline.
- parallel with ground and both feet flat on the floor. This improves blood circulation and 3 Tension Control
- 2 Seat Position Locking with Recliner Synchron Mechanism (M21)

- Turn the tension control knob clockwise for a more rigid back tilt and anti clockwise

for a softer tension to suit control according to your body weight.

- The tension control allows comfortable and relaxed seating according to your body weight.

4 Headrest

- With height and angle adjustment that provide ergonomic support for the neck to prevent cervical strains.

5 Adjustable Armrest (73A)

- Height adjustment armrest with PU padding on top to provide comfortable resting position for the arms.

6 Fixed Armrest (42A)

- Modern design PP injection fixed T-armrest provides a natural resting position for the arms.

7 Gaslift

- With GERMANY DIN 4550 Class 3 Standard passed gaslift.

8 NH1 + R2 Base Roller

- With US BIFMA standard passed sleek nylon high base NH1 with R2 60mm roller.

9 NB5 + R1 Base Roller

- With US BIFMA standard passed nylon flat base NB5 with R1 50mm nylon castor.

10 Cantilever Base (CE42) - Epoxy Black Sledge Base.





No. 2 & 3, Jln Perindustrian Gemilang, Tmn Perindustrian Gemilang, Batu 4, Jln Mersing, 86000 Kluang, Johor, Malaysia. Tel : (+6) 07-7733 292 | Fax : (+6) 07-7739 181

